



Quote Number: 967618
 Opportunity Number: 1650509
 Sourcewell Contract #: 110421-ALT
 Date: 4/26/2022

Quoted for: CITY OF RIVERSIDE (CA)

Customer Contact:

Phone: / Email:

Quoted by: COY HYPES

Phone: / Email:

Altec Account Manager: CHRIS CAMPBELL / JESUS RIOS

REFERENCE ALTEC MODEL		Sourcewell Price
AC18-70B	Hydraulic Telescopic Crane	\$230,430

(A.) SOURCEWELL OPTIONS ON CONTRACT (Unit)

1	AC18-70B-AUTO	Automatic Transmssion	\$9,351
2	AC18-70B-FBO	Front Bumper Outrigger	\$8,000
3	AC18-70B-TANDEM	Tandem axle chassis	\$38,466
4	AC18-70B-UCR	Continuous Rotation (Must Select FBO)	\$9,893

(A.1) SOURCEWELL OPTIONS ON CONTRACT (General)

1	DEL-TRLR	Delivery other than standard drive away service per mile (delivery on trailer)	\$26,850
2	VCAM	Backup Camera System	\$1,313
3	SPOT3	FOUR (4) POINT STROBE SYSTEM (LED)	\$843
4	TBE	ELECTRIC TRAILER BRAKE CONTROLLER. Controls Trailers with Electric Brakes, Wired to 7-Way Plug Next to Pintle Hook	\$324
5			
6			
7			
8			
SOURCEWELL OPTIONS TOTAL:			\$325,471

(B.) OPEN MARKET ITEMS (Customer Requested)

1	UNIT		\$0
2	UNIT & HYDRAULIC ACC		\$0
3	BODY	Altec Custom Body with Front Bulkhead / Sliding Ratchet Binder System / Two (2) Underbody Storage Boxes (36x18x24) / One (1) Underbody Storage Box (60x18x24)	\$14,212
4	BODY & CHASSIS ACC		\$0
5	ELECTRICAL	4wo (2) LED, Spot Lights / Whelen Super LED Light Bar / Whelen Super LED Traffic Advisor with Controller	\$8,765
6	FINISHING	CAL-OSHA	\$857
7	CHASSIS	2025 Freightliner 114SD 6X4; Cummins L9N with Allison 3000RDS Auto Transmission	\$27,250
8	OTHER	Federal Excise Tax (F.E.T.)	\$19,734
OPEN MARKET OPTIONS TOTAL:			\$70,818

SUB-TOTAL FOR UNIT/BODY/CHASSIS: \$396,289

CA Fees: \$400

TOTAL FOR UNIT/BODY/CHASSIS: \$396,689

Pricing valid for 45 days

NOTES

PRICING: Altec will make every effort to honor this quotation, subject to the following provisions. Prices for equipment with production start dates 12 months and beyond are budgetary only due to irregular cost inflation and market volatility. These prices will be reviewed based on market conditions and confirmed closer to the production date. For a quoted chassis model year beyond the current open order bank, chassis model year, specifications and price should be considered estimates only and subject to change. Chassis model year, specifications and price will be reviewed and confirmed when specific model year information becomes available from the OEM.

PAINT COLOR: White to match chassis, unless otherwise specified

WARRANTY: Standard Altec Warranty for Aerials and Derricks - One (1) year parts warranty One (1) year labor warranty Ninety (90)

TO ORDER: To order, please contact the Altec Account Manager listed above.

CHASSIS: Per Altec Commercial Standard

DELIVERY: No later than **31** months ARO, FOB Customer Location

TERMS: Net 30 days

BEST VALUE: Altec boasts the following "Best Value" features: Altec ISO Grip Controls for Extra Protection, Only Lifetime Warranty on Structural Components in Industry, Largest Service Network in Industry (Domestic and Overseas), Altec SENTRY Web/CD Based Training, Dedicated/Direct Gov't Sales Manager, In-Service Training with Every Order.

TRADE-IN: Please ask your Altec Account Manager for more information

BUILD LOCATION: Roanoke, VA



September 28, 2022
Our 93rd Year

Ship To:
CITY OF RIVERSIDE (CA)
ATTN JANENE PURDIE
2911 ADAMS ST
RIVERSIDE, CA 92504
US

Bill To:
CITY OF RIVERSIDE (CA)
FINANCE DEPARTMENT
3900 MAIN ST
RIVERSIDE, CA 92522-0000
United States

Attn:
Phone: 951-826-5548
Email:

Altec Quotation Number: 967618 - 4
Account Manager: Mark James Baldwin
Technical Sales Rep: Coy Hypes

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Unit</u>	
1.	Altec's AC18-70 Hydraulic Telescopic Crane built in accordance to Altec's standard specifications and includes the following features:	1
	A. Maximum Lifting Capacity: 18 ton (16.3 metric ton)	
	B. Boom: 70 foot (21.3 m), 3-Section Proportional	
	C. Sheave Height: 80 foot (24.4 m) on base boom	
	D. Altec LMAP (Load Moment & Area Protection) System: Hirschmann system that includes Rated Capacity Limiter and Working Area Definition Audible Alarm Set-Points. Includes boom angle, length and rotational position.	
	E. Winch: Single speed with burst of speed, 12,000 pound (5,443 kg) line pull on bare drum, mounted at base of boom (unless otherwise stated below in options)	
	F. Lower Winch Control: Located at hook stowage point for ease of unit setup	
	G. Winch Drum Rotation Indicator: Provides tactile and visual indication to operator of which motion, speed, and direction.	
	H. Anti-Two Block Device	
	I. Hydraulic System: Hydraulic pilot operated control valves at the control station	
	J. Control Station(s): Curbside and streetside walk-through control stations with grab handles for bed access	
	K. Operator Controls: Emergency stop, engine start/stop, and crane/outrigger mode switches	
	L. Outrigger Boom Interlock System: Helps prevent operator from using unit until all outriggers are deployed	
	M. Outrigger Motion Alarm: Provides audible alarm when any of the outriggers are in motion	
	N. Outriggers: Primary outriggers are walking beam (pivoting A-frame type) and auxiliary are modified A-frame type (unless otherwise stated below in options)	
	O. Outrigger Controls: Electric over hydraulic controls located at each rear corner of tailshelf providing a line-of-sight from the controls to the outrigger contact zone	
	P. Paint: Altec 2-Stage Powder Coat Paint Process (Altec white is standard unless otherwise stated in options)	
	Q. Complies with ASME B30.5 Mobile Crane Standard	
	R. Manuals: Two (2) Operator's and two (2) Maintenance/Parts manuals	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	S. Basic Operation Videos: DVDs for Crane and LMAP	
2.	Behind Cab Mount	1
3.	Continuous Rotation, installed	1
4.	Heavy Lift	1
5.	Federal Bridge Law Compliance Required	1
6.	Main Winch, 12,000 LB, Single Speed, With Burst Of Speed	1
7.	Wire Rope, Rotation Resistant (Category 2), 240 FT Of 9/16" Diameter	1
8.	Standard Boom Tip Sheave Arrangement	1
9.	ATB Switch Cover	1
10.	Jib Not Required	1
11.	Platform Not Requested	1
12.	AC18 Subbase For A-Frame Outriggers	1
13.	Primary outriggers, walking beam	1
14.	Auxiliary outriggers, A-frame, underframe	1
15.	Front bumper outrigger, with electrical switch control, required for 360 degree working capacity	1
16.	Electric Over Hydraulic Outrigger Controls - Rocker Switches Installed On Tailshelf, Each Side	1
17.	Outrigger Down Jack Controls on Swing Arm for Stand Up Control Stations	1
18.	Dual Walk Through Control Stations Mounted Each Side of Unit Pedestal	1
19.	Left Hand Joystick Control/Right Hand Lever Controls (Standard for all Models)	1
20.	Foot Throttles At Stand Up Control Stations	1
21.	Drum Rotation Indicator, installed	1
22.	Winch Disable Switch	1
23.	Telescope Disable Switch	1
24.	No Radio Remote Requested	1
25.	Hirschmann LMAP System With Swing Arm Mount	1
26.	Vinyl LMAP Display Cover With Altec Logo	1
27.	Imperial/US Units of Measure for Capacity Charts and LMAP System	1
28.	English Language for Capacity Charts, LMAP System, and Placards	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
29.	AC18-70B-HL-ENG	1
30.	Spanner Wrench - Crane Swing Drive Adjustment	1
31.	Outrigger Control Covers, Fold Down	1
32.	Altec Powder Coat Paint Process	1
33.	Base Boom and Turntable Painted Altec White (Standard)	1
34.	Extended Portions of Outriggers Painted Black (Standard)	1
35.	Front Bumper Outrigger Painted Black (Standard)	1
36.	Subbase Painted Black (Standard)	1
37.	Upper Booms Powder Painted Black (Standard)	1
<u>Unit & Hydraulic Acc.</u>		
38.	Load Ball, Non-Swivel, For 9/16" Winch Rope	1
39.	Load Ball Strap For Behind Cab Mounted Unit	1
40.	Load Ball Tie Points	1
41.	Boom Winch Stow at Tailshelf	1
42.	Front Bumper Outrigger Installation Components	1
43.	Frame Stiffeners for Crane Subbase Installation	1
44.	Subbase Installation Components	1
45.	Load block not required	1
46.	No Load Block Holder Required	1
47.	HVI-22 Hydraulic Oil (Standard).	90
48.	Single 90,000 BTU Cooler	1
49.	Standard Pump For PTO	1
50.	Hot shift PTO for automatic transmission	1
51.	Standard Altec PTO/Transmission Functionality with Park Brake Auto Neutral for Allison Automatic Transmissions: -Once the PTO switch is on, the Parking Brake is engaged, and the transmission is in a near stationary condition (i.e., below 5 mph) the transmission will be forced to neutral, and PTO will engage.	1
52.	Standard Parking Brake Machine Interlock	1
53.	70 Gallon Reservoir, On Side Of Frame	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
54.	Additional Unit/Hydraulic Accessory AC45 Bubble Target Levels: - One (1) located at the rear - One (1) located at each control station. Qty:2	3
<u>Body</u>		
55.	Altec Body	1
56.	Steel Body	1
57.	Body Is To Be Built In Accordance With The Following Altec Standard Specifications: A. Basic Body Fabricated From A40 Grade 100% Zinc Alloy Coated Steel. B. All Doors Are Full, Double Paneled, Self-Sealed With Built-In Drainage For Maximum Weather-Tightness. Stainless Steel Hinge Rods Extend Full Length Of Door. C. Heavy-Gauge Welded Steel Frame Construction. D. Integrated Door Header Drip Rail At Top For Maximum Weather Protection. E. Fender Panels Are Either Roll Formed Or Have Neoprene Fenderettes Mechanically Fastened. F. Steel Treated For Improved Primer Bond And Rust Resistance. G. Automotive Type Non-Porous Door Seals Fastened To The Door Facing. H. B-Line Channel Installed In Compartments	1
58.	Platform/Flatbed	1
59.	Finish Paint Flatbed Custom Color (Provide Color And Code) To be painted BLACK (FNLA LV650)	1
60.	Undercoat Body	1
61.	Approximate Flatbed Length (Engineering to Determine Final Length) 234"	1
62.	1/8" (12 Gauge) Treadplate Floor	1
63.	96" Body Width	1
64.	6 Inch High Structural Flatbed Crossmembers	1
65.	Stake Pockets Around Outside Perimeter of Flatbed, Installed on 24" Centers	1
66.	Steel Rub Rails On Side Of Flatbed	1
67.	Light Channels Installed At Rear Of Flatbed	1
68.	Flatbed shipping channel	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
69.	Front bulkhead, full width of flatbed Bulkhead: - To be as tall as possible without interference of the LMAP swing arm. - Top 18" of rack to be expanded metal, remaining portion to be steel plated. - Header to have access doors at the walkthroughs at the control station. - Bulkhead to be removable or allow for access to cover cover and valves.	1
70.	Body plant to provide holes for mounting flatbed to subbase.	1
71.	Custom Additional Flatbed Option Adjustable, Sliding Ratchet Binder System: - To have five (5) binder located on curbside - To have 3" x 3/8" flatbar located on streetside - To have stops over rear axle to not allow contact with tires	1
72.	Additional Steel Underbody Storage Box Underbody, Steel, Storage Box, with Chain Door Holders - To be 36"W x 18"H x 24"D - One (1) to be installed behind the rear outriggers on each side of flatbed. Qty: 2.	2
73.	Additional Steel Underbody Storage Box Underbody, Steel, Storage Box, with Chain Door Holders - To be 60"W x 18"H x 24"D - To be installed forward of rear axles on curbside.	1
74.	Additional Body Option Adjustable sliding binders to have 4" x 20' load steps with flat hook on one end for attachment to flatbar stand off on flatbed. Binders to be installed below the flatbar stand off.	1
75.	PL Designator	1
<u>Body and Chassis Accessories</u>		
76.	ICC (Underride Protection) Bumper Installed At Rear	1
77.	ICC (Underride Protection) bumper with integral fixed Grip Strut steps on curbside and streetside	1
78.	Swivel Style Pintle Hitch (30 000 LB MGTW with 6 000 LB MVL), 11-Bolt T-Mount, Altec Preferred (T-125 Style)	1
79.	Set Of D-Rings for Trailer Safety Chain, installed one each side of towing device mount.	1
80.	Glad Hands At Rear, Straight Type	1
81.	Standard Boom Rest, Removable	1
82.	Wood Outrigger Pad, 24 x 24 x 2.5 Inch, With Rope Handle	5

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
83.	Outrigger Pad Holder, 25x25x8.75, Steel, For Multiple 24x24x3 Outrigger Pads And Smaller, Pendulum Retainer	2
84.	Custom Outrigger Pad Holder Outrigger Pad Holder, Installed On Front Bumper Outrigger, Holds 24" x 2.5" Wooden Pad	1
85.	Cribbing Storage Installed Under Control Station, Streetside	1
86.	Cribbing Storage Installed Under Control Station, Curbside	1
87.	Mud Flap Without Altec Logo (Pair)	1
88.	Quick Release Brackets For Installing Two Mudflaps.	1
89.	Dock Bumpers - Installed at end of Frame Rails	1
90.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1
91.	Wheel Chock Holders (Pair), Single Capacity, With Mudflap Mounting, For Installation Under Flatbed Or Dump Body	1
92.	Triangular Reflector Kit, Shipped Loose	1
93.	5 LB Fire Extinguisher With Light Duty Bracket And Placard, Shipped Loose	1
94.	Vinyl manual pouch for storage of all operator and parts manuals	1
95.	CNG Processing	1

Electrical Accessories

96.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1
97.	4-Corner Strobes, Amber, LED, Two (2) Surface Mounted Lights In Grille, Two (2) Round Lights At Rear	1
98.	Strobe Lights Wired Battery Hot	1
99.	Spot Light, LED, with Chrome Housing, 6" DIA	2
	Details: - Lights to be located on switch box located at each control pod. (PN: 991328299). If not possible, mount one (1) work light each side of bulkhead.	
100.	Dual Tone Back-Up With Outrigger Motion Alarm	1
101.	Altec Backup Camera System, 7" Color LCD Monitor, Heated Infrared Camera with Day/Night Sensor and Audio	1

Monitor to be installed in the chassis cab.

Camera to be installed at the rear of the truck.

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	A. 7" Color LCD Monitor With LED Backlighting And Proximity Indicators	
	B. 2 Inputs With Independent Triggers	
	C. Heated Infrared Camera With Day/Night Sensor And Audio	
	D. Mirror/Normal View	
	E. IP68 Rated	
	F. Wide Viewing Angle (104 Degrees Horizontal x 78 Degrees Vertical)	
	G. 20 Meter Cable Assembly	

102.	Install backup camera monitor on the front windshield in lieu of the rearview mirror.	1
103.	6-Way Trailer Receptacle (Pin Type) Installed At Rear	1
104.	Electric Trailer Brake Controller (Kelsey Hayes #81741)	1
105.	Altec Modular Panel System (AMPS) - Includes Mounting Panel and Accessory Switches	1
106.	Pre-Wired Power Distribution Module - Installed	1
107.	Pre-Wired Power Distribution Module To Non Pre-Wired Chassis Conversion	1
108.	Additional Electrical Accessory	1
	Whelen Super LED Light Bar (Model: FW2AAAA 55") - To be installed on top of the cab.	
109.	Additional Electrical Accessory	1
	Whelen Super LED Traffic Advisor (Model: TA870L); To Include Controller (TACTLD1 TA Controller) - To be installed at the rear	

Installation

110.	Manual Kit Includes (2) Operators Manuals, (2) Parts and Maintenance Manuals	1
------	--	---

Finishing Details

111.	Powder Coat Unit Altec White	1
112.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1
113.	Apply Non-Skid Coating to all walking surfaces	1
114.	English Safety And Instructional Decals	1
115.	Vehicle Height Placard - Installed In Cab	1
116.	Placard, HVI-22 Hydraulic Oil	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
117.	Stability test unit according to ANSI requirements.	1
118.	Completed Test Forms To Be Included In The Manual Pouch	1
	A. Stability Test Form	
	B. Dielectric Test Form (For Insulating Units)	
119.	DOT Certification Required	1
	City of Riverside	
120.	Focus Factory Build	1
121.	Delivery Of Completed Unit	1
122.	Inbound Freight	1
123.	Cal-OSHA Certification	1
	To be completed at SVC CTR	
124.	As Built Electrical And Hydraulic Schematics To Be Included In The Manual Pouch	1
125.	CNG Inspection Processing	1
126.	Final Assembly	1
<u>Chassis</u>		
127.	Altec Supplied Chassis	1
128.	Chassis	1
129.	2025 Model Year	1
130.	Freightliner 114SD	1
131.	Dual Rear Wheel	1
132.	Set Back Axle	1
133.	6x4 Tandem Axle	1
134.	Chassis Cab	1
135.	Regular Cab	1
136.	Chassis Color - White	1
137.	Front Frame Extensions	1
138.	Air Horn Under Cab	1
139.	AM/FM Radio	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
140.	Trailer Air Brake Package	1
141.	Other Clear Cab To Axle Length CA: 102"	1
142.	Chassis Wheelbase Length - 264	1
143.	GVWR 58,000 LBS	1
144.	18,000 LBS Front GAWR	1
145.	40,000 LBS Rear GAWR	1
146.	120,000 Yield Strength (PSI)	1
147.	17.01 - 18.00 Section Modulus	1
148.	Spring Suspension	1
149.	Cummins L9N (Natural Gas)	1
150.	Gaseous Fuels	1
151.	320 HP Engine Rating	1
152.	Allison 3000 RDS Automatic Transmission (Left and Right Side PTO Openings Only)	1
153.	Other Fuel Tank Size 230-064: 60 Gallon CNG Tank, Mounted Back of Cab.	1
154.	Other Exhaust 237-1CH: Vertical Exhaust	1
155.	EPA Emissions	1
156.	Chassis Idle Engine Shut-Down Required	1
157.	315/80R22.5 Front Tire	1
158.	11R22.5 Rear Tire	1
159.	Air Brakes	1
160.	Park Brake In Rear Wheels	1
161.	2 Chassis Batteries	1
162.	Other Battery Capacity (CCA) MIN 2000CCA	1
163.	Battery Under Cab Left Hand	1
164.	Freightliner - Clear Area Around Allison PTO Openings (362-824) and (363-011)	1

We Wish To Thank You For Giving Us The Pleasure
 And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>
165.	Freightliner PTO Throttle Wiring for Automatic Transmission (163-004) (148-074) (87L-003)	1
166.	Freightliner Transmission Dipstick Tube Enters Curbside of Transmission (346-013)	1
167.	Freightliner/Allison Body Builder Connection (34C-001)	1
168.	No Prewire Chassis 296-027: PreWire Package	1
169.	Air Ride Drivers Seat	1
170.	Air Ride Passenger Seat	1

Additional Pricing

171.	Administration Fees	1
172.	Documentation Fees	1
173.	Federal Excise Tax Item: If provided, Quote subtotal is an Estimate only. Final determined at invoicing.	1
174.	California Orders To be delivered to SVC CTR for certifications and LIC/REG. From SVC CTR, unit to be delivered to City of Riverside	1

Miscellaneous

175.	Standard Altec Crane/HiLine Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, five (5) year structural warranty	1
------	---	---

Altec Industries, Inc.

BY



Coy Hypes

Notes:

1 Altec will make every effort to honor this quotation, subject to the following provisions. Prices for equipment with production start dates 12 months and beyond are budgetary only due to irregular cost inflation and market volatility. These prices will be reviewed based on market conditions and confirmed closer to the production date.

For a quoted chassis model year beyond the current open order bank, chassis model year, specifications and price should be considered estimates only and subject to change. Chassis model year, specifications

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

CERTIFIED AS TO FUNDS AVAILABILITY:

UTILITY EQUIPMENT AND SERVICES SINCE 1988

BY: 
ASSISTANT CHIEF FINANCIAL OFFICER

and price will be reviewed and confirmed when specific model year information becomes available from the OEM.

- 2 Altec takes pride in offering solutions that provide a safer work environment for our customers. In an effort to focus on safety, we would encourage you to consider the following items:

Outrigger pads (When Applicable)
Fall Protection System
Fire extinguisher/DOT kit
Platform Liner (When Applicable)
Altec Sentry Training
Wheel Chocks

The aforementioned equipment can be offered in our new equipment quotations. If you find that any of these items have not been listed as priced options with an item number in the body of your quotation and are required by your company, we would encourage you to contact your Altec Account Manager and have an updated quote version sent to you. These options must be listed with an item number in the quotation for them to be supplied by Altec.

- 3 The final fully loaded weight of the truck and structural ratings of the hitch assembly may reduce the towing capacity and the vertical load capacity of the finished truck. These capacities may not match the ratings of the chassis or hitch.

- 4 Altec Extended Warranty Option:

An Altec Extended Warranty is an extension of Altec's Limited Warranty and protects you from the repair cost associated with defects of materials and workmanship after the standard Limited Warranty expires.

Altec offers many types of coverages and coverage packages. Ask your Altec account manager for details. Quotes are available upon request.

- 5 Unless otherwise noted, all measurements used in this quote are based on a 40 inch (1016mm) chassis frame height and standard cab height for standard configurations.

- 6 Altec Standard Warranty:

One (1) year parts warranty.

One (1) year labor warranty.

Ninety (90) days warranty for travel charges.

Warranty on structural integrity of the following major components is to be warranted for so long as the initial purchaser owns the product: Booms, boom articulation links, hydraulic cylinder structures, outrigger weldments, pedestals, subbases and turntables.

Altec is to supply a self-directed, computer based training (CBT) program. This program will provide basic instruction in the safe operation of this aerial device. This program will also include and explain ANSI and OSHA requirements related to the proper use and operation of this unit.

Altec offers its standard limited warranty with the Altec supplied components which make up the Altec Unit and its installation, but expressly disclaims any and all warranties, liabilities, and responsibilities, including any implied warranties of fitness for a particular purpose and merchantability, for any customer supplied parts

Altec designs and manufactures to applicable Federal Motor Vehicle Safety and DOT standards

7 Price does not reflect any local, state or Federal Excise Taxes (F.E.T). The quote also does not reflect any local title or licensing fees. All appropriate taxes will be added to the final price in accordance with regulations in effect at time of invoicing.

8 F.O.B. - Destination

9 Altec values your data privacy. The Altec Family of Companies (including Altec, Inc., and it's subsidiaries) may collect telematics data from the equipment you own. Please review Altec's Equipment Data Privacy Notice on www.altec.com for more information. By purchasing equipment from Altec, you consent to Altec's right to collect and use such data.

10 Interest charge of 1/2% per month to be added for late payment.

11 Changes made to this order may affect whether or not this vehicle is subject to F.E.T. A review will be made at the time of invoicing and any applicable F.E.T. will be added to the invoice amount.

12 Trade-in offer is conditional upon equipment being maintained to DOT (Department of Transportation) operating and safety standards and remaining in compliance of DOT until arrival at an Altec Facility. This will include, but is not limited to engine, tires, lights, brakes, glass, etc. All equipment, i.e., jibs, winches, pintle hooks, trailer connectors, etc., are to remain with unit unless otherwise agreed upon in writing by both parties. ALTEC Industries reserves the right to re-negotiate its trade-in offer if these conditions are not met.

All reasonable and necessary expenses required of ALTEC Industries to execute transportation of the trade-in will be invoiced to the customer for payment if these conditions are not met to maintain DOT standards.

Customer may exercise the option to rescind this agreement in writing within sixty (60) days after receipt of purchase order. After that time ALTEC Industries will expect receipt of trade-in vehicle upon delivery of new equipment as part of the terms of the purchase order unless other arrangements have been made.

13 Any payment made by a credit card may be subject to a surcharge fee.

14 Estimated Delivery: 31 months after receipt of order PROVIDING:
A. Customer supplied chassis is received a minimum of sixty (60) days before scheduled delivery.
B. Customer approval drawings are returned by requested date.
C. Customer supplied accessories are received by date necessary for compliance with scheduled delivery.
D. Customer expectations are accurately captured prior to major components being ordered (body, chassis) and line set date. Unexpected additions or changes made after this time or at a customer inspection will delay the delivery of the vehicle.

Estimated Delivery is based on information at time of quote and is subject to change.

Altec reserves the right to change suppliers in order to meet customer delivery requirements, unless specifically identified, by the customer, during the quote and or ordering process.

15 After the initial warranty period, Altec Industries, Inc. offers mobile service units, in-shop service and same day parts shipments on most parts from service locations nationwide at an additional competitive labor and parts rate. Call 877-GO-ALTEC for all of your Parts and Service needs.

16 This quotation is valid until APR 29,2022. After this date, please contact Altec Industries, Inc. for a possible extension.

17 FINANCING AVAILABLE: Please contact Altec Capital at (888) 408-8148 or email finance@altec.com for more information.

18 Please direct all questions to Mark James Baldwin at (540) 992-5300

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

**DELIVERY AND ACCEPTANCE CERTIFICATE
ALTEC CAPITAL SERVICES, LLC**

Lease Number: TBD

Description	Serial #	Vin
AC18	TBD	TBD

By signing below I represent, warrant and agree on behalf of the Lessee named above:

1. I HAVE INSPECTED THE EQUIPMENT AND ACCEPT THE EQUIPMENT FOR ALL PURPOSES UNDER THE LEASE ON BEHALF OF THE LESSEE.
2. The Equipment is of the correct size, design, capacity and manufacture, as selected by the Lessee. It is in good condition and is working properly and has been delivered or installed in a satisfactory manner. The Equipment is suitable for the Lessee's purposes. If any portion of the Equipment has not been delivered or installed at the time I sign this document, the Lessee assumes all risk and responsibility, waives any right to reject the Equipment or revoke acceptance and agrees not to hold the Lessor responsible for delivery or installation of the Equipment.
3. I acknowledge that the Lessor is not the manufacturer of the Equipment or the manufacturer's agent and waive any defenses the Lessee may have now or in the future against the Lessor.
4. I acknowledge that the Lessor is relying on this Certificate in paying for the Equipment and that the inspection is my responsibility. I have had the opportunity to inspect the Equipment and to reject it. I accept the Equipment AS IS, WHERE IS. I confirm that the Lease is in full force and effect and that neither the Lessee nor the Lessor is in default under the Lease. MY SIGNING BELOW MAKES THE LEASE A NON-CANCELLABLE, UNCONDITIONAL OBLIGATION OF THE LESSEE.
5. I represent and warrant that I have the authority to execute this Certificate of Acceptance and Lessee authorizes Lessor to write in the Acceptance Date following telephone confirmation by Lessee of its receipt of the equipment (although I acknowledge that the Lessor is under no obligation to request such oral confirmation and that it is not a condition of acceptance of the Equipment).

DO NOT SIGN UNTIL EQUIPMENT HAS BEEN DELIVERED AND INSPECTED
DO NOT SIGN IF EQUIPMENT IS UNACCEPTABLE FOR ANY REASON

Lessee: City of Riverside / Riverside Public Utilities

By: _____
Title: _____
Date: _____

Date: 10/11/2022
Quote #: 22-0249

Altec Quotation

Altec Associate: Chris Campbell

Customer: City of Riverside

1. FA#: - In-service date: - Equipment type: AT37G,TA60, AC18 D4065, D3055, D20
Year: - Make: - Model: -

Available Options

Semi-Annual PM Inspection

	<u>AT37G</u>	<u>D2000-4000</u>	<u>TA60</u>	<u>AC18</u>
6 Year Pre-paid Maintenance	\$5,425	\$13,414	\$8,568	\$21,826
7 Year Pre-paid Maintenance	\$6,427	\$15,891	\$10,150	\$25,855
8 Year Pre-paid Maintenance	\$7,458	\$18,441	\$11,779	\$30,005

DOT Inspection

	<u>ALL UNITS</u>
6 Year DOT	\$917
7 Year DOT	\$1,088
8 Year DOT	\$1,263

Quarterly BIT Inspection

	<u>ALL UNITS</u>
6 Year BIT	\$2,751
7 Year BIT	\$3,264
8 Year BIT	\$3,789

Dielectric Test

	<u>AT, D2-4, TA ONLY</u>
6 Year Dielectric	\$1,625
7 Year Dielectric	\$1,913
8 Year Dielectric	\$2,207

Semi-Annual PM Travel

	<u>ALL UNITS</u>
6 Year Travel	\$4,830
7 Year Travel	\$5,722
8 Year Travel	\$6,640

Repair Central Services

6- year Service Lease Prepaid Package	\$1,224
7- year Service Lease Prepaid Package	\$1,428
8- year Service Lease Prepaid Package	\$1,632

Prepaid maintenance contracts include all labor and materials associated with that maintenance action. Additional repairs or work outside the scope of normal maintenance are not covered by these contracts. Prepaid maintenance travel coverage is capped at 3 hours for service calls to locations with a single unit. If PM service calls are for multiple units at a single location to be performed on the same trip the travel cap may be waived.

This quotation is valid for 30 days. Visit www.Altec.com/service/fleet-services or email fleetservices@altec.com for more information about what Altec Fleet Services can do for you!

