

## City of Riverside Roadway Capacity<sup>(1)</sup>

Roadway Classification	Number of Lanes	Two-Way Traffic Volume (ADT) <sup>(2)</sup>		
		Service Level C	Service Level D	Service Level E
Local	2	2,500-2,799	2,800-3,099	3,100+
Collector (66' or 80')	2	9,900-11,199	11,200-12,499	12,500+
Arterial <sup>(3)</sup>	2	14,400-16,199	16,200-17,999	18,000+
Arterial (88')	4	16,800-19,399	19,400-21,199	22,000+
Arterial (100')	4	26,200-29,599	29,600-32,999	33,000+
Arterial (120')	6	38,700-44,099	44,100-49,499	49,500+
Arterial (144')	8	50,600-57,799	57,800-64,999	65,000+

**Notes:** (1) All capacity figures are based on optimum conditions and are intended as guidelines for planning purposes only  
(2) Maximum two-way ADT values are based on the 1999 Modified Highway Capacity Manual Level of Service Tables  
(3) Two-lane roadways designated as future arterials that conform to arterial design standards for vertical and horizontal alignments are analyzed as arterials.

Mission Inn Ave between Redwood Dr & Arfon Way = 26,380 ADT = Need 4 travel lanes (2 in each direction)

Mission Inn Ave between Redwood Dr & Pine St = 13,584 ADT = Need 2 travel lanes (1 in each direction)